



- Auger Drive
 - Post Hole Borer
 - Micro Excavator 750Kg-2T

AUGER

- POST HOLE BORER ::
- MACHINES 750KG-5T ::
- MACHINES 5T-10T ::
- MACHINES 10T-30T ::
- MACHINES 20T-50T ::
- AUGER EXTENSIONS ::
- AUGER WEARPARTS ::

QUICK LINKS

- HOME ::
- ABOUT DIGGA ::
- WHY DIGGA ::
- MEDIA GALLERY ::
- LATEST NEWS ::
- PRODUCT REGISTRATION ::
- ASK US A QUESTION ::
- CONTACT US ::

[PRINT VERSION](#) // [VIEW WARRANTY INFO](#)

A6 - Soil Augers


The A6 range of Soil Augers are specially designed for Excavators up to 10 tonne to drill in earth. The augers are available with a range of different teeth options to suit most ground conditions including earth, hard soils, shale, clay, and permafrost.

Digga manufactures premium performance Augers in England for distribution throughout Europe through our dealer network. All Digga Soil Augers are built from high grade steel and feature ideal flight pitches and advanced cutting head design providing superior drilling performance. Over 30 years of design and development has produced the highest quality range of soil augers on the market today.

Can't get your old teeth out? Digga's ingenious Knock In, Knock Out tooth locking system (PADLOC) eliminates the need for cumbersome tools to remove the auger teeth.

A6 Auger Specifications

	DESCRIPTION
DRIVE SUITABILITY	PD4 / PD4HF / PD5 / PD6 PD6HF / PD7 / PD8 / PD8HF PD10 / PD10HF
SUITS MACHINES	5T - 10T
STANDARD HUB	SQUARE
HUB OPTIONS	57 MM SQUARE / 75 MM SQUARE
DIAMETER	150 - 1500 MM
OVERALL LENGTH	1500 MM
FX	8 MM
TEETH	MEDIUM [TM]



RC6 - Combination Earth and Rock Augers

Our RC6 Augers are specially designed for Excavators up to 10 tonne to drill in earth, shale, clay, permafrost asphalt, and fracturable rock drilling. The RC6's rock auger teeth are easy to install and remove with an ingenious Knock In, Knock Out tooth locking system which eliminates the need to use extra tools to remove the teeth.

RC6 Auger Specifications

	DESCRIPTION
DRIVE SUITABILITY	PD4 / PD4HF / PD5 / PD6 PD6HF / PD7 / PD8 / PD8HF PD10 / PD10HF
SUITS MACHINES	5T - 10T
STANDARD HUB	SQUARE
HUB OPTIONS	57 MM SQUARE / 75 MM SQUARE
DIAMETER	150 - 1500 MM
OVERALL LENGTH	1500 MM
FX	8 MM
TEETH	ROCK [TT]

